



SRX-R515P

The SRX-R515 is a high quality 4K digital cinema projection system.

Pricing available upon request

UPC: 027242278660

Overview

The SRX-R515 is a high quality 4K digital cinema projection system designed for use in small or medium sized screen auditorium with a user-friendly design and lower cost of ownership. The projection system, which has a smaller body than the SRX-R320, is fully DCI compliant and boasts design features that make it more cost effective and simple-to-use. These include a lower cost light source system that allows easy and safe lamp replacement, a washable air filter, a single 15-inch GUI control panel and iPad and Android tablet support for remote operations.

This projection system is ideal for independent cinemas, and offers true 4K quality from the lens to the integrated media block. It features an improved SXRD optical engine, high contrast ratio of 8000:1, 15,000 lumens brightness, easy-on-the-eye Sony 3D, and high frame rate capabilities up to 60 frames per second. The system also features high-speed content ingest/transfer and high capacity storage.

Highlights

- * Great Image Quality: True 4K (SXRD and lens), Easy-on-eye 3D (Parallel), and High Contrast (average 8,000:1)
- * Easy To Use: Easy and safety replacement and redundant lamp system, Small in size, Single UI, tablet support*, large storage capacity, high speed ingestion
- * Low running cost: Low lamp cost, Reusable filter, High efficient 3D system
- * The screen coverage is up to 12.5m**.
- * DCI Compliance
- * Support 2K 3D HFR (48P/60P) as standard
- * Two HDMI input for alternative content

Specifications

General Specifications	Detail
Dimensions (W x H x D)	W548 x H634 x D1119 mm*1
Power Requirements	AC 200 to 240V, 50-60Hz, Single-phase, 21.5A to 18A
Power Consumption	450W lamp: Max. 4.3kW 330W lamp: Max. 3.2kW
Optical Specifications	Detail
Resolution	4096 x 2160
Light Output	15,000 lm (450W lamp) / 11,000 lm (330W lamp)
Lamp	6 x HPM lamps*
Image Device	3 x 1.48 inch 4K SXRD
Contrast Ratio	8,000:1

Other Specifications	Detail
Safety Regulations	[Digital Cinema Projector SRX-R515] VCCI Class A, UL 60950-1, CSA C22.2 No.60950-1, FCC/IC Class A Digital Device, IEC 60950-1, EN 60950-1, EN 55022 Class A + EN 55024, EN 61000-3-11 + EN 61000-3-12, AS/NZS CISPR22 (EN 55022) Class A [Digital Cinema Server XCT-S10] VCCI Class A, UL 60950-1, CSA C22.2 No.60950-1, FCC/IC Class A Digital Device, IEC 60950-1, EN60950-1, EN 55022 Class A + EN 55024, EN 61000-3-2 + EN 61000-3-3, AS/NZS CISPR22 (EN 55022) Class A [Touch Panel Monitor LKRA-007] VCCI Class A, FCC/IC Class A Digital Device, EN 55022 Class A + EN 55024, AS/NZS CISPR22 (EN 55022) Class A

Accessories

Supplied Accessories

Model:	Description:	U.S.List Price
	[Digital Cinema Projector SRX-R515] Keys for removing panels (5), Safety regulations (1), TPC arm (1 set), Cable clasper (2) [Digital Cinema Server XCT-S10] Feet (1 set), PCI express cable (2m) (1), Ethernet cable (2m) (1) [Touch Panel Monitor LKRA-007] AC adaptor (1), VGA cable (1), USB cable (1)	Pricing available upon request

Optional Accessories

Model:	Description:	U.S.List Price
	2D Projection lens LKRL-Z511/514/519	Pricing available upon request
	3D Projection Lens and 3D Lens filter LKRL-A502/503LKRA-005	Pricing available upon request
	Projection Lamp LKRM-U450/330	Pricing available upon request
	Lens Change Table LKRA-008	Pricing available upon request